AD-780 081

METHODOLOGY INVESTIGATION: TECHNICAL EVALUATION OF FIELD ARTILLERY DIGITAL AUTOMATIC COMPUTER (FADAC) TAPES

Donald H. McCoy

Army Test and Evaluation Command Aberdeen Proving Ground, Maryland

13 August 1973

DISTRIBUTED BY:



National Technical Information Service
U. S. DEPARTMENT OF COMMERCE
5285 Port Royal Road, Springfield Va. 22151

OUCTV2 21 LTED		THOM AUI					
Security Classification	<i>F</i>	D 780 081					
DOCUMENT CONT	ROL DATA - R & D .	•					
(Security classification of title, body of obstract and indexing	annotation must be entered who	n the everell report to classified)					
ORIGINATING ACTIVITY (Corporate author)	1	RT SECURITY CLASSIFICATION					
Systems Analysis Directorate		UNCLASSIFIED					
US Army Test and Evaluation Command	28. SROU	•					
Aberdeen Proving Ground, Maryland 21005							
Technical Evaluation of FADAC Tapes							
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)							
Methodology Investigation, Final Report	August 1	L973					
8. AUTHOR(S) (Piret name, middle initial, last name)		······································					
Donald H. McCoy							
AEPORT DATE	74. TOTAL NO. OF PAGES	78. NO. OF REPS					
13 August 1973	¥ 23	2					
Se. CONTRACT OR GRANT NO.	M. ORIGINATOR'S REPORT	NUMBER(\$)					
S. PROJECT NO.							
a. PROJECT NO.							
c.	AL ATHER REPORT HOUSE	Any other numbers that may be seeigned					
•	this report)	the state of the s					
₫.							
10. DISTRIBUTION STATEMENT	A						
approved for subbe release	e distribution	unlimited.					
	, _						
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY						
		Directorate, AMSTE-SY,					
		en Proving Ground, MD					
	1 21005						

This st .dy was conducted by the Systems Analysis Directorate of Headquarters, US Army Test and Evaluation Command, for the purpose of demonstrating the need and feasibility of complete technical testing of revised FADAC tapes. Better technical testing was shown to be feasible and desirable. Recommendations were made to have Frankford Arsenal conduct completely automated technical tests.

> NATIONAL TECHNICAL INFORMATION SERVICE 1) A Department of Companies Springfield VA 22151

Security Classification LINK B LINK A LINK C KEY WORDS ROLE ROLE WT ROLE WT WT FADAC Computers Software Automated Testing Test Methodology

UNCLASSIFIED

METHODOLOGY INVESTIGATION

FINAL REPORT

TECHNICAL EVALUATION OF

FIELD ARTILLERY DIGITAL AUTOMATIC COMPUTER (FADAC) TAPES

BY

DONALD H. McCOY 13 AUGUS: 1973

The second second second

FOREWORD. Acknowledgement is given to Ms. Joyce Brunsell for her computer support effort and Mrs. Evelyn Lidke and Mrs. Joyce Roszak for manuscript preparation.

Preceding page blank

TABLE OF CONTENTS

																										PAGE
	TRACT EWORD	•	• •	•		S1	EC'	•	•		•	•		•	٠	•	•	•	•	•	•	•	•	•	•	111 1v
1.	BACKGROUN	D		•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1
2.	OBJECTIVE	S		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	1
3.	DETAILS O	F :	THE	I	NVI	ES?	ric	GA?	ri(ON		•	•	•	•	•	•	•	•	•	•	•	•	•	•	1
4.	CONCLUSIO	NS			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	3
5.	RECOMMEND	AT:	ION	s.	•	•	•	•	•	•	•	•	•	•	•	•		•		•		•	•	•	•	3
					SI	2C?	CIC	N	I	<u>.</u>		\PI	?El	ND:	ICI	<u>es</u>										
A.	CORRESPON	DEI	NCE		•	•		•	٠	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	A-1
В.	REFERENCE	S	• •	•	•	•		•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	B-1
c.	DATA	•		•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•		•	•	•	•	C-1
D.	DISTRIBUT	TO	N I	TST	Г.	_																				D-1

SECTION I. SUMMARY

1. BACKGROUND.

This report concludes a methodology investigation concerning technical testing of Field Artillery Digital Automatic Computer (FADAC) tapes conducted by the Systems Analysis Directorate, US Army Test and Evaluation Command (TECOM). The Methodology Proposal is inclosed in Appendix A. The purpose of the investigation was to determine the feasibility of conducting a technical evaluation of revised FADAC tapes using an automated procedure.

These tapes are created by US Army Weapons Command (WECOM) (Software Engineering Branch, Fire Control Division, Frankford Arsenal) and tested by TECOM (the Field Artillery Board). During testing, problems of a technical nature and operational nature are being confounded. An attempt is made to simultaneously test the technical correctness of the revised tape, as well as user problems, i.e., the capability of man-machine interaction.

This work was done in conjunction with the Firing Tables Branch of the Ballistic Research Laboratories (BRL) and Frankford Arsenal (FA). BRL supplied the necessary trajectory data (see Appendix C); FA made the necessary FADAC runs. The major thrust of the Systems Analysis effort was to fully automate an already existing ballistic test procedure and to investigate other areas of testing where automation should be accomplished.

2. OBJECTIVES.

The primary objectives of this investigation are (1) to demonstrate that technical and service testing of revised FADAC tapes can and should be separated; and (2) to determine the feasibility of fully automating the technical testing.

3. <u>DETAILS OF THE INVESTIGATION</u>.

During the lifetime of FADAC, at least five major revisions have been implemented. Both Frankford Arsenal and the Field Artillery Board have stated that the testing situation is unsatisfactory. No effort is made in this study to ascertain the exact reasons. The pursuit of this task would be counterproductive. Hopefully, fully automated technical testing will alleviate the old problems associated with each revision of the FADAC tapes.

Frankford Arsenal has, in fact, partially automated the testing of ballistic programs for FADAC. This is done by operating two FADACs in a tandem arrangement (see Figure 1). One of the FADACs is used as an input/output (I/O) driver for the other FADAC, which is loaded with the ballistic program to be tested. The I/O driver replaces the man-in-the-loop. The driver bypasses the keyboard and causes the test results to be written on a teletype. The test is conducted free of operator error. This is an ideal situation for technical testing; i.e., testing which is conducted to determine if the FADAC is performing accurately for known test scenarios.

The Systems Analysis Directorate wrote a computer program to automatically generate the large number of inputs required for the Field Artillery Board automated ballistic test procedure. This program, contained in Appendix B, voids the requirement for Field Artillery Eoard to manually prepare exhaustive input in order to completely check out the ballistic programs. The complete test cycle is shown in Figure 2.

A sample of the output from this program is shown in Figure 3. The appearance of the output is rather confusing; however, once the basic concept is understood, it is really quite simple. A pair of digits addresses the particular position on the FADAC input matrix and the value required for input follows, separated by delimiters.

The output from this program is used to drive the ballistic test. Hardcopy output from a sample run is shown in Figure 4. A "C" in Column 1 indicates the correct solution. The "true" answers and the FADAC answers, labeled "F", which do not agree within a preset tolerance are flagged with a "\$\$".

In order to conduct the investigation, two basic training exercises were necessary. First, the format of the BRL tapes was studied. The BRL tapes contain trajectory data for a weapon/charge combination that are included in the FADAC programs. A conservative estimate of the number of cases run is 50,000. Second, the format of the automatic ballistic test program input had to be learned.

A delimiter is a special character used to separate items in an input list. The delimiter in this case is a "+".

To test the concept, some 2,000 into a for the 155mm Howitzer were generated. A subject of these 2,00 was randomly selected and run on the tandem FADACs. Sample inputs and outputs from these runs were as shown in Figures 2 and 4.

Approximately 60 problems per hour can be run in the auto-test mode, versus about 20 per hour in the manual mode. This timing consideration is important since there are at least 350 test problems that can be run for every weapon/ammunition charge/fuze combination. Also, testing in the automatic mode can be easily rerun and retesting in FADAC has been a common problem.

If the user and the developer cooperate in this effort, a testbed or benchmark set of problems should evolve which will eliminate virtually all technical test problems.

4. CONCLUSIONS.

Since the trial with the ballistic procedure ws successful, there is no reason to believe that other facets of technical testing will be unsuccessful. Additional work is required to automate the chronograph, registration, trilateration and survey programs.

5. RECOMMENDATIONS.

A letter has been sent to US Army Armament Command (ARMCOM) (see Appendix B) which includes the recommendations of this study. The recommendations are essentially the following:

- (1) Complete technical testing of revised FADAC tapes is required.
 - (2) Technical testing should precede service testing.
- (3) Frankford Arsenal should be responsible for technical testing.
 - (4) TECOM should observe all technical testing.
- (5) TECOM should conduct service tests upon satisfactory completion of technical tests.
- (6) Action should be taken to develop automated testing procedures for the survey, chronograph, trilateration, and registration problems.

a top worth the more thanks into




Figure 1. Auto-Ballistic Test Configuration




Figure 2. Automatic Input and Auto-Ballistic Test Configuration

```
&&I+01+--99+21+1+27+9+23+9+26+1--45+1+3303+ 1209+&0+ 50+--00+1+
                                                                   2+ 6.3+ 20
&&1002+--99+21+1+22+9+23+9+26+2--45+1+3300+ 1209+&0+ 3J+--00+1+
                                                                   2+ 6.5+ 20
&&1003+--99+21+1+22+9+23+9+26+3--45+1+3300+ 1209+&0+ 3)+--09+1+
                                                                   2+ 6+0+ 20
&&1004+--99+21+1+22+9+23+9+26+7--45+1+3300+-1209+&0+-30+--00+1+
                                                                   2+ .6.2+ 20
&&1005+--99+21+1+22+0+23+9+26+1--45+1+3300+ 29&8+&0+ 50+--00+1+
                                                                  38+3 +. R+110
&&1006+--99+21+1+27+0+23+9+26+2--45+1+3300+ 2988+&0+ 30+--00+1+
                                                                  38+35.3+110
&&1007+--99+21+1+22+0+23+9+26+3--45+1+3300+ 2988+&0+ 50+--00+1+
                                                                  38+35.0+110
E61009+--99+21+1+22+0+23+9+26+7--45+1+3300+ 2989+6C+ 30+--00+1+
                                                                  38+34.4+113
&&ZUO1+--99+Z1+1+Z2+0+23+9+Z6+1--45+1+QQ75+ 3Z97+&0+Z00+--00+1+3ZZ8+36.3+110
&&2002+--99+21+1+22+0+23+9+26+2--45+1+0075+ 3297+&0+189+--09+1+3229+36.8+110
&&2003+--99+21+1+22+0+23+9+26+3--45+1+0075+ 3297+&0+200+--00+1+3228+36-0+110
&&2004+--94+21+1+22+0+23+9+26+7--45+1+0075+ 3297+&0+180+--00+1+3223+35.9+110
&&3U01+--99+21+1+22+0+23+9+26+1--45+1+6115+ 2868+&0+1U0+--00+1+4830+34,1+110
& 6300 2+--99+21+1+22+0+23+9+26+2--45+1+6115+ 2368+60+ 30+--00+1+4830+34.5+110
&&3003+--99+21+1+22+0+23+9+26+3--45+1+6115+ .2868+&0+100+--00+144830+34+0+110
&&3004+--99+21+1+22+0+23+9+26+7--45+1+6115+ 2863+&O+ 30+--00+1+4830+33.7+110
&&4001+--99+21+1*22+0+23+9+26+1--45+1+4*35+ 3302+&C+150+--00+1+1631+36.3+110
$$4003+--99.+71+1+27+0+23+9+26+3--45+1+4435+ 3302+80+150+--00+1+1631+36.0+110 $$$4004+--99+21+1+22+0+23+9+26*7--45+1+4435+ 3302+80+130+--00+1+1631+35.9+110
```

Figure 3. Sample Input for the Auto-Ballistic Test

2201

¥ 04 #2	101	COMP			
		DEFL	TF	Œ	
V C	1	2	6.3	200	
F	1	2	6.4	200	
Pic#14	cw l	Curr		_	
CU	CHC	re Fl.	1F	Œ	
N C	1	2 2	6.3	200	
٧F			6.4	200	
PR #2	2201	COMP			
$\mathbf{\omega}$	CHG	DE FL	TF	Œ	
C	1	3 2 2 8	363	1160	
-	1	3 2 2 8	36.3	1160	
PR #20	06.1	COMP	TF.		
æ	CHG	DEFL	TF 36.3	<u> </u>	
C_	1	28	36.3 37.6	ששוו	
F	1	3 23 5	37.6	1115	\$\$
PR #23	301	COMP	•	~~	
m	CHG.	UEFL	Tr	Œ	
ياي	• • •	4636	34.5 34.4	1160	
P		4030	34.4	יששוו	
PK #5	איש ו כער	CONP.	76	Œ	
L C	CHG	UE FL	TF		
. • -	-	3 @ 4833	34.1 34.5	1166	\$\$
DD #2	1.31	COMP	34.5	1100	"
FR #4	CHG	OF EI	TF	Œ	
w	CHG	1421	360	1100	
-	, '	1631	36.0 36.0	1100	
		COMP	J 0 .D	1100	
(U)	CHC	DE FI	TF	Œ	
2	1	DE FL	363	1100	
F	i	1636	37.2	1116	55
•	•	1000	7 · ••		••

Figure 4. Sample Output for the Auto-Ballistic Test

SECTION II. APPENDICES

APPENDIX A. CORRESPONDENCE

COPY

DISPOSITION FORM

AMSTE-ME

SUBJECT: Technical Evaluation of FADAC Tapes

TO Dir, Systems Analysis FROM Meth Imprv Dir DATE 29 Mar 74 CMT 1 LTC Stone/dg/5145

- 1. Request you conduct subject investigation in accordance with the attached Methodology Investigation Proposal.
- 2. Funds in the amount of \$3,500 have been authorized to support the effort. These funds include \$1,000 to support travel. In order to cite these funds the methodology X Order should be used in conjunction with the Systems Analysis Cost Center. The remaining funds are designated for the support of field effort in the event it is decided to task APG computer program preparation. In such cases the funds will be distributed to APG as needed by this Directorate.

1 Incl MIP /s/ W. L. Stone LTC /for/ SIDNEY WISE Director

Systems Analysis Directorate US ARMY TEST AND EVALUATION COMMAND

Methodology Investigation Proposal, FY 73 9 March 1973

- 1. TITLE: Technical Evaluation of FADAC Tapes.
- 2. INSTALLATION: HQ. TECOM.
- 3. PRINCIPAL INVESTIGATOR: Donald H. McCoy, Systems Analysis Directorate, AMSTE-SY, AUTOVON 870-2093.
- 4. STATEMENT OF THE PROBLEM: WECOM periodically provides new tapes for the FADAC fielded system. This action establishes the precedence for TECOM's role in post-deployment of all future fielded computer systems. The current testing program at the Field Artillery Board combines both technical and user evaluation of a new FADAC tape. For the latest revision, five weeks per tape is required to conduct the evaluation. A significant portion of this time is used to input a large number of test cases by hand. This study will investigate the feasibility of conducting technical evaluation of FADAC tapes automatically.
- 5. <u>DESCRIPTION OF THE INVESTIGATION</u>. a. Systems Analysis Directorate will determine whether the technique currently used by Frankford Arsenal to evaluate new FADAC tapes can be extended to permit direct inputting of BRL trajectory data (on tape) into FADAC. Currently, Frankford Arsenal tests new tapes by connecting two FADACsin tandem, and using one FADAC as the input/output driver to the other FADAC. The input to FADAC must be keypunched from BRL printouts and converted to paper-type.
- b. Systems Analysis Directorate will determine the feasibility of preparing a computer program that will convert the BRI tape format into the FADAC input format. If it is estimated that 0.5 manmonths of effort is required to write the computer program, Analytic Branch, MTD will be tasked to prepare the computer program. If APG does not have the resources available to complete the task in the required time frame, Systems Analysis Directorate will prepare the program.
- c. Upon completion of the conversion program, the tape for the M109Al will be evaluated using two FADACs in tandem. This will conclusively establish the feasibility of conducting technical evaluation of FADAC tapes automatically.
- d. A TOP will be prepared detailing the procedures for the technical evaluation of FADAC tapes.

7. JUSTIFICATION: A significant reduction of total test time will result if TECOM can evaluate the technical aspects of FADAC tapes automatically. Furthermore, a more thorough checkout of the tapes can be performed by using more test cases.

9. RESOURCES REQUIRED:

Manmonths	Source	<u>Salaries</u>	TDY
2 1	HQ, TECOM APG	2000	1000 500 1500

10. SCHEDULE: Final report due 30 June 1973.

A PERSONAL PROPERTY AND A PERS

AMSTE-SY

30 JUL 1973

SUBJECT: Technical Testing of Revised FADAC Tapes

Commander
US Army Armament Command
Rock Island, Illinois 61201

1. Reference conversation between CG, TECOM, and CG, ARMCOM, on above subject at the AMC Summer Commanders' Conference on 13 July 1973, and meetings held between Mr. Harold Brodkin, Fire Control Development and Engineering Directorate, Frankford Arsenal, and Mr. Donald H. McCoy Headquarters, TECOM, on 15 February, 16 April, 17 May, and 23 May 1973.

2. Background.

- a. The Field Artillery Digital Automatic Computer (FADAC) is a fire control computer for cannon artillery. The computer is a second generation device with limited memory (8,192 words), utilizing machine language programming. The FADAC peripheral devices include a keyboard input, low-speed paper tape, high-speed paper tape, and a teletype output.
- b. Frankford Arsenal (FA) has the responsibility for providing software (cannon program tapes) for the FADAC system. This includes ballistic programs, as well as auxiliary functions like the survey and transfer programs. FA coordinates the need with the user before updating and revising these programs. TECOM (the Field Artillery Board) has the responsibility for product improvement tests of these tapes.
- c. Since the original fielding of FADAC, the cannon programs have been updated and reissued at least five times. Theoretically, there should be no technical errors in these tapes when they are released to TECOM for testing. On every release, however, major problems have been found by the Field Artillery Board (FABD). This means FA must correct the software and send the corrected tape to the FABD for retesting. This Headquarters believes the "find-fix loop" can be avoided by a thorough technical test of the software tapes prior to the FABD tests.
- d. FA has taken the basic steps toward an automated technical test procedure by automating a ballistic test routine. This routine uses one FADAC

30 JUL 1973

AMSTE-SY

SUBJECT: Technical Testing of Revised FADAC Tapes

computer as an input/output driver for testing the ballistic routines. A similar procedure can and should be developed for the survey, trilateration, chronograph and K-transfer programs.

- e. The Systems Analysis Directorate at this Headquarters has written a computer program which augments the FA automated ballistic test procedure. This program is designed to automatically create input to the FA test program from Ballistic Research Laboratories (BRL) test data tapes. In the past, hand preparation of the BRL input on punched cards was prohibitive, and precluded a complete technical test of a ballistic tape for all fuze/projectile combinations. The automatic preparation of these inputs means that a complete technical test of a ballistic tape can now be easily accommodated in a timely and efficient manner.
- 3. As indicated by the reference above, TECOM and FA have been actively working to solve some mutual problems. The solutions to these problems concerning technical testing of FADAC software require a more formal arrangement between ARMCOM and TECOM. Therefore, TECOM recommends that:
- a. TECOM and ARMCOM initiate action to develop a mutually agreeable baseline for an automated technical test procedure for FADAC tapes.
- b. FA be responsible for the technical testing, to include a complete check of the ballistic programs and all auxiliary functions.
 - c. TECOM witness these tests.
- d. Upon completion of technical testing, these tapes be submitted to TECOM for service testing.
- e. Action be taken to develop automated testing procedures for the survey, chronograph, trilateration and K-transfer programs.
- 4. The Systems Analysis Directorate, Headquarters, TECOM, will continue to actively support the automation aspects of this effort. The technical point of contact is Mr. Donald H. McCoy, AUTOVON 870-2093.
- 5. The Field Artillery Materiel Testing Directorate, Headquarters, TECOM, will provide technical assistance and will effect coordination with the Field Artillery Board. The point of contact is Mr. Emmet O'Brien, AUTOVON 870-4875.

CHARLES P. BROWN Major General, USA Commanding

CF:

Cdr, Frankford Arsenal

ATTN: SARFA-N-7400 (Mr Brodkin)

A-5

APPENDIX B. REFERENCES

- 1. FM 6-40-3, Operation of the Gun Direction Computer M18, Cannon Gunnery Application, August 1970.
- 2. Theodore Lafferty, Jr. and Harry Onsey, Cannon Artillery Ballistic Programs for Computer, Gun Direction, M18 (FADAC). Report R-1976, Frankford Arsenal, July 1970.

1. FADAC PROGRAM:

```
DIMENSTIN 4(41), 8(2",5"), 44PK(2")
   DIMENSION RUFF(201, ICF (4), IDELY(4)
   DIMENSION ICTAZIA), METNICA), IFT (4), LMFT(4)
   INTEGER CHGTYP, TRAJNO, CT1, CT2
   DATA ISTAT/133131, 100751, 161151, 144351/
   DATA METN/161, 161, 1411, 1421/
  DATA TET/1.2.3.7/
   DATA 175 /3,3203,4800,1600/
   CATA OSO , WETA, CTI, CT2, PLNK / IN SOF, IA
                                              . 1 41
                                                      . * G *
   PATA TRAJE TOAT
   7678 MARK /234112341/
   DATA LMET/4+1/
  LL =0
   nn 9 L=1.13
 1 RFAD(9.2.FRP=98.FND=991A
 2 FORMAT(4'44)
   IF ((A(15).NF.TOA).AND. (A(35).NF.TRA))GO TO L
   IF(A(35). FQ. TPA) GO TO 12
  nn 3 1=1,20
   A(1,1) = A(1)
 3 9(1.2)=5(1+27)
   JCTART=3
  50 TO 13
12 07 14 1=1,20
14 8(1,1)=4(1+20)
   JSTAPT=2
13 NO 4 J=JSTART,49,2
   J7FL=J-1
   READ(9,2, FRR=98, FND=90) A
   1F(A(15).FO. TRA) GO TO 5
   IF (A (35) . FO. TRA) GO TO 15
   20 6 1=1,27
  (1) A=(L,1) A
 6 B(T, J+1)=4(T+27)
   50 TO 4
15 JOEL = JOCL+1
   00 16 1=1.21
16 P([.J)=A(T)
   67 17 5
 4 CONTINUE
 5 N=JDEL
  BACKSPACE 9
  WRITE(6, 7) MARK
 7 FORMAT(14,2044)
  N,1=L P CO
  WRITE(6,7)(P(T,J),1=1,23)
 R CONTINUE
  LEN=80
   MUINAT
   IF(A(7.N).FQ.957.CP.A(7."-31.FQ.757)G7 TO 9
   CALL COPETRUFF, LEN'
                                                               C-1
   AP [TF( NOUM, 311 (R(K, 4) +K=1+20)
```

```
CALL CORECRUSE, LFN.
   READ ( VOUM. 32) TRAJUD. MET
31 FORMAT(2044)
32 FTRMATITIX .12.47)
   IF ( MET. EQ. METAIGH TO 9
   CALL CORFIRMEF, LEN)
   WRITE(NOUM, 31) (R(K,11
                            ),K=1,201
   CALL COPF(BUFF, LEN)
   PEACINOUM, 331 TOF
33 FORMAT(2X,14)
   IF(10F.GT.800)GO TO 34
   L?41=9
   GO TO 35
34 LOHI=0
35 CALL CORFIGHEF, LEND
   WRITE(NOIM, 31)(R(K,12 ),K=1,20)
   CALL CORFIGHEF, LENT
   PFAT(NOUM, 36) ICHGNO, CHGTYP
36 FORMAT(464, 11, A1)
   IF(CHGTYP.ED.CT1)CHGTYP=0
   IF(CHGTYP.FQ.CT2)CHGTYP=9
   JREC=N-1
   IF (B(1.N). FQ. RLNK) JRFC = N+4
   CALL CORFIGUEF, LENT
   W9 [ T = ( NOUY , 3 | ) ( B ( K , JR = C ) , K = 1 , 20 )
   CALL CORECBUFF, LFN1
   READ (NDIM, 37) THE, IF, HEEL
37 FORMATIES. 0, 9x, 15, 15x, F6. 0)
   IDFFL=DFFL+.5
   TTOF=TOF+.5
   TF=ITOF
   JPFC=JPFC+1
   CALL COPE(BUFF, LEN)
   WRITE(NDUM, 31) (R(K, JRFC), K=1,20)
   CALL CORFIBUFF, LENT
   READ(NOUM, 38) FS1, FS2
38 FORMAT(39X, 2F6. 0)
   WPITE(6.39)TRAINC.MET.IOF.LOHI.ICHGNO.CHGTYP.TE.IDEFL.ITDF.FSI.
  1FC2
39 FORMAT(//14,12,1X,42,1x,7(15,1X),2(F6,2)//)
   99 49 JMFT=1,4
   IF (MET. NF. METN (JMET) 1 GO TO 40
   IGT=[GTAZ(JMFT]
   LL =L WET (JVET)
   [MFT(JMET) = [MFT(JMFT) + 4
   IDEFL=IDEFL+IDF(JMFT)
   GO TO 45
40 CONTINUE
45 77 41 L70P=1.4
   IDN=JMFT+Innn+LL+LNPP-1
   IV=[DELY(JMFT)
   IFZTYP=IFT(( 10P)
   TE(TET(LCOP).FQ.1)
                        TV=TV+2()
   IFILONP. EQ. 31 GO TO 42
   IF (LIOP.EQ.1) FS = TOF
   IF (LOOP.F9.2) FS=FS2
   IF(L)OP.FO.4) FS=FS1
   WPITE(6,43) IPN, ICHGNO, LOHI, CHGTYP, IFZTYP, IGT, IE, IY, ICHGNO,
  *IDEFL, FS, IQF
   WRITE(7,53) IPN, IC"GNO, LOHI, CHGTYP, IF7TYP, IST, IF, IY, ICHGNO,
  *IDEFL.FS.IDF
```

```
---99+21+', Il, '+22+', Il, '+23+', Il, '+26+', Il,
  2F4.1,1+1,[4,1+1]
. 53 FORMAT! '66',14,
                    '+--99+21+',|1,'+22+',|1,'+23+',|1,'+26+',|1,
       '--45+1+',A4,'+',I5,'+&0+',I3,'+--00+',I1,'+',I4,'+',
  2F4.1, "+", [4, "+")
   GO TO 41
42 IF (LOHI.FQ.O) IY=IY+20
   WRITE(6,43) IPN, ICHGNO, LOHI, CHGTYP, IFZTYP, IGT, IE, IY, ICHGNO,
  lidefl, TF , IQF
   WRITE(7,53) IPN, ICHGNO, LOHI, CHGTYP, IFZTYP, IGT, IE, IY, ICHGNO,
  11DEFL,TF
             , I QE
41 CONTINUE
 9 CONTINUE
   GO TO 99
98 WRITE(6,17)A
17 FORMAT(1X,20A4//20A4)
   WRITE(6,18)
18 FORMATI' ERR ACTION LABEL')
   DEBUG SUBCHK
99 CALL EXIT
   END
```

2. SAMPLE TRAJECTORY DATA:

TRAJECTORY NO. 28

FLFV 34LL. MYLS COFF.	LAT M/S	V STD. A7 L9 MILS	HGT TG	T HGT	MDP	CHARGE	N FACTOR		IV ACT	LB
	207.	3 95. 1095.		0.0			-0.460			75•00
CORR. U29CT TOF	RANGE U3DOT		E2 4ACH	F3 PETARD		FS	Ul	U2	- U3	דחמוט
	-		NO.	COFFF.						
5 T C	9,0	4	4	M	MILS	4/5	4/5	M/S	M/S	4/5**2
M/S**?	4/5**2			1/SEC	M564	4520				
0.00	0.	0.	0.	0.	0.00	207.3	97.7	182.8	0.0	-0.9
-11.4		0.0500		-0.0086						•••
7-1.01	97.			-0.	0.15			171.6	-0.0	-0.8
-11.2		0.0500		-0.0090	0.9					4.0
2,02		194,		-0.	0.32			160.5	0.0	-0.7
-11.0		0.0500		-0.0075				1000	3.0	00,
1. 3.02		290.			0.49			149.6	0.0	-0.7
-10.3		0.0500		-0.0070	2.9			14.40	3.0	•••
4.03		385.	642.		0.68	-		138.8	0.0	-0.6
-10.7		0.0500		-0.1065	3.9			1304.0	0.0	•••
5.04	_	479.	776.		0.99			128.2	0.0	-0.6
-10.6	_	0.0500		-0.0061	4.9					•
-						,,,				
17.84	1639.	1639.	1581	٠.	5.58	89.2	99.2	0.0	0.1	-0.3
-9.8		0.0500	_	-0.0032						44
•										
36.37	3207.	3207.	-0.	3.	42.98	198.2	81.7	-160.6	^.3	-^.6
-8.5	0.01	0.0500								